

CONFORMITIES/STANDARDS

CE, ANSI, CSA, AS/NZS approved

DESCRIPTION

- Enjoy the ultimate in clarity and crystal-clear vision with the Eclipse 2.0. Super Bright Vision: Shade 2.0 at light state, light transmittance up to 30%. Provides welders with superior clarity and visual acuity.

Specifications/Technical Data	
Optical Class	1/1/1/2
Viewing Area	96.00 x 46.50mm
ADF Size	110 x 90 x 9mm
Lens Shade	DIN 4-8/9-13 Variable
Light State	DIN 2.0
Shade Control	Internal
Sensors	4
Grind Mode	Yes (internal)
On/Off	Automatic sleep mode
Power Supply	Solar cell. Replaceable battery (1xCR2450 lithium)
Switching Time	1/25,000 s
Sensitivity Control	Yes - Internal LCD
Delay Time (dark to light)	0.05 - 1.0s LED and Button Control



COLOUR AVAILABILITY

c CAMO

SIZE AVAILABILITY

ONE SIZE - ONE SIZE

Low Amp TIG Rated	>=2amps/DC; >=2amps/AC
Application Range	Stick Welding (DC&AC); TIG(DC,DC Pulse);TIG AC(Pulse),Excellent low amperage TIG response; MIG/MAG ;MIG/MAG Pulse;Plasma Cutting/ Welding; Grinding; Not for Laser Welding or Oxyacetylene Welding/Cutting